

# **KEYLOK Fortress Flash Drive®**

Building a Secure Software Environment



Fortress Flash dongles provide the same Fortress protection and licensing capabilities along with partitionable flash store (8GB). Used for distributing applications and data storage. Auto-run enables users to run the application directly from the dongle.

#### Overview

- ✓ Extended memory provides additional security and licensing options
- ✓ CodeVault offers enhanced security through execution of application code on the dongle
- ✓ Smart card processor
- ✓ Extensive API library enables rapid & simple implementation

#### **Features**

- ✓ Driverless
- √ Windows, Mac, Linux (including ARM)
- ✓ Protect multiple applications with one device
- ✓ Use multiple dongles on a single server (Windows)
- ✓ Available for Networks (Windows) to enforce concurrent usage
- ✓ Implement creative licensing models including Expiration Date, Features and Counters
- ✓ Remote Update dongles in the field
- ✓ 5,000 55,000 bytes read/write programmable memory
- ✓ CodeVault for enhanced security
- ✓ Smart card processor

### **OS and Development Tools**

Operating Systems	Development Tools
Windows XP (32/64 bit) and newer	Borland C/C++
Linux 2.4 and newer (incl. ARM)	Delphi
MAC OSX	Intel Fortran
UNIX	Java
Ubuntu 13.1 x64 x86 / 12.04 x32 x64	Linux (C, Java)
Fedora V18 x64 x86	Microsoft Access
OpenSUSE 13.1 x32 x64	Microsoft Visual Basic
CentOS 6.5 x32 x64	Microsoft Visual Studio (C/C++/C#)
	PERL
	VB.Net



## **Technical Specifications**

Environment		
Storage Temperature	-10° F to 175°F (-23° C to 80° C)	
Operating Temperature	32° F to 157° F (+0° C to +70° C)	
Dimensions / Connectors		
Fortress Flash Drive USB	50mmx19mmx7mm Standard USB port	
Memory		
Туре	Programmable memory	
Data retention	At least 10 years	
Programming RAM	5,120 bytes = 2560 memory locations 18,944 bytes = 9472 memory locations 50,560 bytes = 25280 memory locations 1 Million Write cycles per location Unlimited Read cycles	
Security		
Encryption	Proprietary Encryption Algorithms	
Authentication Password	2 <sup>96</sup> possibilities	
Read Password	2 <sup>128</sup> possibilities	
Write Password	2 <sup>176</sup> possibilities	
Smartcard	ISO/IEC 15408 Security Evaluation Level EAL 5+ Highest level globally	
Power	No more than 15 milliamps / Battery on RTC lasts up to 3 years	